



WASHINGTON ALLOY'S Quality  
Management System is  
Certified to **ISO 9001:2008**  
Cert # 05-R0925

# 71T-11 Carbon Steel Gasless Welding Wire

U.S. ALLOY CO.  
dba Washington Alloy  
7010-G Reames Rd.  
Charlotte, NC 28216  
[www.weldingwire.com](http://www.weldingwire.com)



**American Welding Society**  
Sustaining Company Member



## ALLOY DESCRIPTION AND APPLICATION;

71T-11 is a self-shielding flux cored wire designed for single or multi pass welding having a smooth spray-type transfer commonly used on mild steels less than 3/4" thick. Easy general all position wire to use in the field where shielding gas is not practical. Limit to three passes will ensure properties on the mechanicals and weld deposit chemistry.

## TYPICAL FCAW WELDING PROCEDURES; DCEN

Wire Diameter	Wire Speed (ipm)	Amps	Volts	Electrical Stickout
0.030	60- <b>175</b> -200	30- <b>115</b> -200	14- <b>15</b> -18	3/8-1/2
0.035	40- <b>210</b> -240	50- <b>150</b> -220	13- <b>17</b> -19	3/8-1/2
0.045	50- <b>170</b> -200	80- <b>180</b> -220	13- <b>17</b> -20	3/8-5/8
1/16"	60- <b>100</b> -180	120- <b>185</b> -300	15- <b>16</b> -20	1/2-1"

Procedures may vary with change in position, base metals, filler metals, equipment and other changes.

## TYPICAL WIRE CHEMISTRY (%) AND WELD METAL PROPERTIES;

	AWS Spec.	U.S. ALLOY 71T-11		AWS Spec	Typical
Carbon	0.30 max	0.10			
Manganese	1.75 max	0.55	Tensile Strength (psi)	70-95,000	77,000
Silicon	0.60 max	0.10	Yield Strength (psi)	58,000 min.	70,000
Aluminum	1.80 max	1.20	Elongation in 2"	20% min.	22%
Phosphorus	0.030 max.	0.016			
Sulfur	0.030 max.	0.006			

**AVAILABLE SIZES:** TW 71T-11= Spools of .030, .035, .045, .068, 1/16, 5/64

**SPECIFICATIONS;** ANSI/AWS A5.20                      E71T-11  
ASME SFA A5.20                                      E71T-11

**EAST COAST**  
7010-G Reames Rd  
Charlotte, NC 28216  
Tel (888) 522-8296  
Fax (704)598-6673

**GULF COAST**  
4755 Alpine Drive #100A  
Stafford, TX 77477  
Tel (877) 711-9274  
Fax (281)313-6332

**WEST COAST**  
8535 Utica Ave  
Rancho Cucamonga, CA 91730  
Tel(800)830-9033  
Fax (909)291-4586



2012 DC

Warehouse Distribution Center – Dayton, Ohio

Head Office – Puyallup, Washington

Washington Alloy Company believes that all information and data given is correct. Use this information to assist in making your own evaluations or decisions and this information should not be mistaken as an expressed or implied warranty. U.S. ALLOY CO. assumes no liability for results or damages incurred from the use of any information contained herein, in whole or in part.