

# WASHINGTON ALLOY CO.

## ELECTRODE OVENS

for re-conditioning and storing of stainless, low hydrogen,  
low alloy and all other flux-coated welding electrodes



### 20 lb Capacity

pt no. WA EQ20Si

- \* 250 watts, 220v-110v standard, 70v-48v optional settings
- \* Adjustable external thermostat 175 -300 F (80-150 C)
- \* Outer Dimensions - 23.25 x 7 x 7" (590 x 180 x 180mm)
- \* Inside Dimensions - 19x4.25x4.25" (480 x 110x 110mm)
- \* Net Weight 15.75 lb (7.15Kg)
- \* Mica band heating element /1.5" Glass wool insulation
- \* Powder coated steel, fixed carry handle, LED indicator.



### 50 lb Capacity

pt no. WA EQ 50Si

- \* 350 watts, 220v-110v standard, 70v-48v optional settings
- \* Adjustable external thermostat 175 -300 F (80-150 C)
- \* Outer Dimensions - 22.50 x 9 x 9" (570 x 232 x 232mm)
- \* Inside Dimensions - 18 x 6 x 6" (480 x 110 x 110mm)
- \* Net Weight 33 lb(15Kg)
- \* Mica band heating element /1.5" Glass wool insulation
- \* Powder coated steel, Pull-out carry handle, LED indicator.



### 50 lb Capacity

pt no. WA EQ 50SiW

**Same as above, but with heavy duty rubber wheels  
and a collapsible pull handle.**

**Ideal for moving full ovens accross solid floors,  
(not designed for use on gravel or loose ground)**

Larger ovens are available with capacities of 100lb and above,  
Price and lead times are available upon request.

All ovens and their components are manufactured by a UL approved facility and  
manufacturing procedure, which includes a "burn in" product test on each unit, prior to  
shipping. Replacement thermostats and heating elements are available.



WA.ALLOY CO

California:  
8535 Utica Ave  
Rancho Cucamonga, CA 91730  
(800) 830-9033 T  
(909) 291-4586 F

Texas:  
4755 Alpine Drive #100A  
Stafford, TX 77477  
(877)711-9274 T  
(281) 313-6332 F

North Carolina:  
7010-G Reames Rd  
Charlotte, NC 28216  
(888)522-8296 T  
(704) 598-6673 F